



**ENGINEERED
ASSEMBLIES**



GENTAS PHENOLIC PANELS FOR RVRS



Gentas uses the world's top quality materials working with prestigious brands across the globe. Gentas has been operating since 1972, with extensive knowledge and reach in the façade industry.

Gentas solid phenolic panels offer hundreds of design options that can be used individually; supporting a design concept, or combined to create something truly unique. Strength and quality of the panels is directly proportional to the quality of the ingredients contained in kraft papers, decorative papers and resins used.







ADVANTAGES

- 400+ colours
- Panel optimization available
- Fire rated version available
- Proven projects across the globe
- No maintenance required



GENTAS PHENOLIC PANELS FOR RVRS

- Gentas panels are available in wood, stone, solid colours and patterns.
- Gentas offers two panel sizes: The minimum panel size is 1300mm x 2800mm (4.3' x 9.2') with the maximum size of 1300mm x 3050mm (4.3' x 10').
- Thicknesses range from 6mm to 20mm.
- 8mm is recommended for facades, and suits Exposed Fasteners or Hidden Fasteners (HF) with Bearclaw using Dynamic Bond.
- 10mm is recommended for soffits, and suits all attachment methods.

Texture	8mm	10mm	Size (mm)	Exposed Fastener	HF with Dynamic Bond	HF with Fastener
Smooth	✓	✓	1300x2800 mm	✓	✓	✓
Smooth	✓	✓	1300x3050 mm	✓	✓	✓

ATTACHMENT METHODS

- 1 Exposed fasteners, typically colour matched rivets, requires 8mm thick panel minimum.
- 2 Hidden Fastener (HF) with Bearclaw using Dynamic Bond, requires 8mm thick panel minimum.
- 3 Hidden Fastener (HF) with fastener, requires 10mm thick panel minimum.

CONTACT:

EngineeredAssemblies.com

1-866-591-7021

info@engineeredassemblies.com

#brilliantbuildings

